IP Security Cam

A02-WIPCAM-11B / A02-IPCAM

NETWORKING

where solutions begin

PLUS

- Local and Remote Monitoring
- Lan/WLan IP interface
- Management software included
- ActiveX control and Java applet supported
- Image capture and video recording
- Motion detection (software)
- Easy to use

HELP DESK SERVICE

FAST SWAP 3 YEARS WARRANTY

WHY TO BUY

The IP Security Cam provides the perfect solution for delivery video over any network employed for remote monitoring or transmitting real-time images over the Internet or Intranet. The IP Security Camera is a standalone system with build-in CPU and WEB based solutions connecting directly to Fast Ethernet (Model A02-WIPCAM-11B also supported by the flexibility of wireless transmission based on the IEEE802.11b standard). It can be managed remotely, accessed and controlled from any PC/Notebook over the Internet or Intranet via a web browser (with streaming video) everyday, everywhere.

IP Security Cam

A02-WIPCAM-11B / A02-IPCAM

where solutions begin

NETWORKING

IPView SE Included



Technical Features:

Video specification:

Resolution:	640 x 480 pixel
Sensor:	1/3" color CMOS sensor
Gain control:	Automatic
Exposure:	Automatic
White Balance:	Automatic
Shutter:	Electronics 1/60 ~ 1/15000 sec
Minimum Illumination:	2.5lux@f1.4, 3000K color
Focal Length:	6.0 mm
Aperture:	F=1.8
Focus Extent:	20 cm - Inf
Lens mounting:	Fixed board lens

Image (Video Setting)

Image compression:	JPEG
Frame rate:	20fps@SIF, 6fps@VGA
Compression Rate selection:	Auto
Frame rate setting:	1, 5, 7, 15, 20, auto (depends on the video format)
Video resolution:	320x240, 640x480
Brightness control:	Range 1- 128
Contrast control:	Range 1- 128
Saturation Control:	Yes

Hardware Interface

LAN Connector:	One RJ-45 port to connect to 10/100Mbps Ethernet, auto-sensed
Wireless LAN:	Built-in 802.11b (Wi-Fi compliant) wireless LAN module (A02-WIPCAM-11B)
LED Indicator:	Power LED (Green), Link LED (Yellow)
Power Supply:	DC 5V, switching type
Power Communication:	6.5 Watt (1300mA x 5V)
Antenna Connector:	1 connectors (A02-WIPCAM-11B)

Communication Support

Communication:	10/100Mbps Ethernet and 802.11b wireless LAN.
Encryption:	64 bit, 128 bit or OFF
Communication protocol:	HTTP, FTP, TCP/IP, UDP, ARP, ICMP, BOOTP, RARP, DHCP, PPPoE

Browser Support (System requirement)

CPU:	Pentium II, 266 MHz or above
Memory Size:	32 MB (64 MB recommended)
VGA card resolution:	800x600 or above

Internet Explorer 5.0 or above (ActiveX Mode View Image supports Internet Explorer under Windows OS)
Netscape 6.0 or above

IPView SE Application

Operating System:	Win 98 SE, Win 2000, Win Me, Win XP
CPU:	Pentium III, 450 MHz or above
Memory Size:	128 MB (256 MB recommended)
VGA card resolution:	800x600 or above

Operating environment

Operating temperature:	5°C ~ 50°C
Storage temperature:	-25°C ~ 50°C
Humidity:	5% ~ 95% non-condensing

Package contents

IP Security Cam or IP Security Cam Wireles
Antenna (A02-WIPCAM-11B), Camera Stand Accessory, RJ-45 Ethernet Cable (Cat 5), Power adapter suitable for your country's electric power, Quick Installation Guide
CD-ROM with Xplug Control (ActiveX module), IPView SE Application Software and User's Guide

WARRANTY 36 MONTHS "ON SITE"!

This ATLANTIS LAND® Networking product is warranted for 36 months with immediate substitution .

Due to the absolute relevance of this product ATLANTIS LAND® will send directly to the final customer the new substitutive product as soon as it will receive information about the defect and it will also retire the previous product . For defect we mean any kind of non functioning with the exclusion of natural phenomena and clear fraud.

The instructions for obtaining the substitution are wrote down in the hand book attached to the ATLANTIS LAND® product and on the web site www.atlantis-land.com.

PRODUCT: IP Security Cam Wired CODE: A02-IPCAM EAN CODE: 8026974009506	PRODUCT: IP Security Cam Wireless CODE: A02-WIPCAM-11B EAN CODE: 8026974009513

HEADQUARTERS & EUROPE:
Atlantis Land S.p.A.
viale De Gasperi, 122
Mazzo di Rho - MI - Italy
info@atlantis-land.com
sales.@atlantis-land.com

ASIA:
Atlantis Land Technology L.t.d.
3rd. Floor, Jonsim Palace
228 Queen's Road East.
Wanchai, Honk Kong
info.hk@atlantis-land.com
sales.hk@atlantis-land.com

INTERNATIONAL SALES FRANCE:
Atlantis Land France
57, Rue d'Amsterdam
75008 Paris - France
info.fr@atlantis-land.com
sales.fr@atlantis-land.com

FAR EAST & USA SALES:
Atlantis Land
International Sales Office
N°. 249 Hsining South Rd.
Taipei - Taiwan
info.tw@atlantis-land.com
sales.tw@atlantis-land.com